

## NTPM 100A-DI / 110A-DI - Smart Energy Sensor



### Features

- ✓ Measures over 100 electrical energy parameters
- ✓ Three-phase and single-phase installations
- ✓ Power quality analysis
- ✓ Full internet connectivity through standard Ethernet interface
- ✓ Embedded rule engine for event driven control
- ✓ Digital outputs for control functions
- ✓ Integrated alarm system
- ✓ Internal memory holds years of data
- ✓ Integrated webserver
- ✓ Web-based user interface
- ✓ DIN rail mount
- ✓ Compact design
- ✓ LVD and EMC compliant

### Overview

Unique solution that combines monitoring of electrical energy consumption, power quality analysis and management of electrical energy use in a single powerful instrument.

NTPM devices can be easily installed and use in any energy management scenario.

Built in Web server enables easy remote control and configuration, as well as real-time monitoring of measured parameters.

Real-time readings

Daily, weekly, monthly trends and graphs



## Electrical characteristics

### Power supply

<b>Voltage</b>	100-270 V AC $\pm 10\%$ Overvoltage category II per IEC 61010-1:2010
<b>Frequency</b>	50/60 Hz $\pm 10\%$
<b>Power consumption</b>	Max 2.5 W

### Voltage inputs

<b>Measured voltage (Un)</b>	Up to 400 V L-N / 690 V L-L (Wye) or 600 V L-L (Delta) UL listed up to 347 V L-N / 600 V L-L
<b>Measurement by voltage transformer</b>	Supported external VT with ratio up to 350
<b>Measurement category</b>	CAT III 600 V per IEC 61010-2-030
<b>Frequency range(configurable)</b>	47 – 53 Hz (50 Hz nominal)
	57 – 63 Hz (60 Hz nominal)
<b>Network type</b>	Single-phase / Two-phase / Two-phase with neutral / Three-phase / Three-phase with neutral
<b>Impedance</b>	5 M $\Omega$
<b>Overload</b>	1.15 Un

### Current inputs

<b>Maximum CT primary</b>	5000 A
<b>Rated input current (Ib)</b>	5 A
<b>Supported CT</b>	Supported external CT with ratio up to 1000
<b>Measured current</b>	Up to 5000 mA
<b>Starting current</b>	0.001 Ib
<b>Permissible current overload</b>	6A continuous
	20 A 10 sec
	50 A 1 sec
<b>Frequency range (configurable)</b>	47 – 53 (50 Hz nominal)
	57 – 63 (60 Hz nominal)

### Measuring characteristics

<b>Accuracy class</b>	0.5
<b>Active power measurement precisions class</b>	0.5
<b>Reactive power measurement precision class</b>	0.5
<b>Power factor (PW) precision class</b>	0.5
<b>Frequency measurement precision class</b>	0.5
<b>Voltage harmonics</b>	up to 31 <sup>st</sup> harmonic
<b>Current harmonics</b>	up to 31 <sup>st</sup> harmonic
<b>Sampling rate</b>	64 samples / cycle

### Relay outputs

<b>Number of outputs</b>	2
<b>Type</b>	General purpose
<b>Maximum load voltage</b>	250 V AC / 30 V DC
<b>Maximum load current</b>	1 A

## Digital outputs

Number of outputs	1
Type	Form A solid state relay
Maximum load voltage	30 V AC / 60 V DC
Maximum load current	125 mA
ON resistance	8 $\Omega$
Isolation	2500 V RMS for 1 minute

## Digital inputs

Number of inputs	3
Type	Externally excited
Voltage OFF	0 – 9.4 V DC
Voltage ON	10.5 – 60 V DC
Frequency	max 4 kHz
Isolation	2500 V RMS for 1 minute
Input burden	max 150 mW at 60 V DC, 60 mW at 24 V DC

## Communication

Interfaces	10/100Mbps Ethernet	1 port
		Modbus TCP, ICMP server, DHCP client, Lan Discovery, Web server
Protocols		Modbus TCP
		Modbus RTU

## Mechanical characteristics

Dimensions	88 x 94 x 58 mm (5 modules)	
Net weight	300 g	
Case	Material	Plastic, PC (UL 94 V-0)
	Mounting	35 mm DIN rail
	IP degree of protection	<IP40


## Environment

Operating temperature	-25 to 70 C°
Storage temperature	-40 to 80 C°
Relative humidity	5 to 95 % non-condensing
Altitude	<2000 m
Pollution degree	2

## EMC (Electromagnetic compatibility)

Harmonic emissions	IEC 61000-3-2	class A
Flicker limitations	IEC 61000-3-3	Compliant
Immunity to ESD	IEC 61000-4-2	Level 4
Immunity to radiated fields	IEC 61000-4-3	Level 3
Immunity to fast transients	IEC 61000-4-4	Level 4
Immunity to surges	IEC 61000-4-5	Level 4
Conducted RF disturbances	IEC 61000-4-6	Level 3
Immunity to magnetic fields	IEC 61000-4-8	Level 3
Immunity to voltage dips and interruptions	IEC 61000-4-11	Compliant
Radiated RF emissions	EN 55011 + EN 55016-2-3	Class A
Conducted RF emissions	EN 55011 + EN 55016-2-1	Class A

## Safety

 Compliant to Low Voltage Directive 2014/35/EU and EMC Directive 2014/30/EU	
Standards	EN 61010-1:2010
	EN 61010-2-030:2010
	EN 61326-1:2013
	EN 61000-6-2:2005 + AC:2005
	EN 61000-6-4:2007 + A1:2011
Protection class	Class II according to EN 61010-1:2010 Double insulated for user accessible parts

## Sustainability

EU RoHS Directive	Compliant
Toxic heavy metal free	Yes
Mercury free	Yes
WEEE	At its end of service life, the product must be disposed of and recycled following specific waste collection regulations on EU markets.

Netico GmbH  
Kummruetistrasse 103, 8810 Horgen, CH  
Tel: +41 43 810 45 22 | +381 18 4516 603  
[info@netico-group.com](mailto:info@netico-group.com) | [www.netico-group.com](http://www.netico-group.com)

 **NETICO**  
A New Kind of Automation